

Storage Recommendations for KYDEX® 5555, KYDEX® 6565, and KYDEX® 6565(d)

TB - 140-G

Recommended Storage Procedure


Palletized Material

KYDEX® 5555, 6565, and 6565(d)

SEKISUI SPI recommends a method similar to standard export packaging practice would be best. This procedure will help protect the sheets during handling, keep the sheets clean, and will minimize moisture absorption.

***Original KYDEX® sheet orders incorporate all the items listed below on each pallet or staple box. If these items are no longer available, a comparable substitute may be used.*

- 1) Place a piece of dunage (scrap sheet) directly on the pallet.
- 2) Center a sheet of moisture wrap on the dunage sheet (SEKISUI SPI uses a paper-based moisture wrap that is coated with a waxy film on one side, which always faces the outside of the package). Allow for enough excess paper on all sides to reach the top of the sheets when you are finished stacking the material. If one sheet of moisture wrap is not wide enough, you may need to tape two sheets together.
- 3) Stack the sheet on top of the moisture wrap.
- 4) Place a sheet of moisture wrap on top of the stack of material with the waxy side up. Fold the excess wrapping material from the bottom over the moisture wrap on top (taking care not to tear holes in the wrap), and seal all seams with clear packing tape.
- 5) Place a piece of dunage on top of the wrapped package. Secure the package together by placing bands as appropriate around the plastic to keep the sheets from shifting during handling. Then shrink wrap the package (similar to wrapping a clear plastic wrap around the edges of the sheets).
- 6) Now place a cardboard lid, or other form of protective covering on top of the package, and band the stack to the pallet as is appropriate.
- 7) Store in a cool dry place out of direct sunlight and not above 120°F (49°C).



SEKISUI SPI
ISO 9001 and 14001 Certified

Customer Service
6685 Low St, Bloomsburg, PA 17815 USA
Phone: 800.325.3133, +1.570.389.5810
Outside the US: +1.570.389.5814
Fax: 800.452.0155, +1.570.387.7786
Email: info@sekisui-spi.com

Technical Service
Phone: 800.682.8758
Fax: +1.570.387.8722
Outside the US: +1.570.387.6997
techservice@sekisui-spi.com

sekisui-spi.com

Storage Recommendations for KYDEX® 5555, KYDEX® 6565, and KYDEX® 6565(d)

TB - 140-G

Recommended Storage Procedure

Palletized Material

KYDEX® 100 and T

SEKISUI SPI recommends a method similar to standard export packaging practice would be best. This procedure will help protect the sheets during handling, keep the sheets clean, and will minimize moisture absorption.

***Original KYDEX® sheet orders incorporate all the items listed below on each pallet or staple box. If these items are no longer available, a comparable substitute may be used.*

- 1) Place a piece of dunnage (scrap sheet) directly on the pallet.
- 2) Stack the sheet on top of the dunnage sheet.
- 3) Place a piece of dunnage on top of the sheet.
- 4) Secure the package together by placing bands as appropriate around the plastic to keep the sheets from shifting during handling.
- 5) Then shrink wrap the package (similar to wrapping a clear plastic wrap around the edges of the sheets).
- 6) Now place a cardboard lid, or other form of protective covering on top of the package, and band the stack to the pallet as is appropriate.
- 7) Store in a cool dry place out of direct sunlight and not above 120°F (49°C).

SEKISUI SPI

ISO 9001 and 14001 Certified

Customer Service

6685 Low St, Bloomsburg, PA 17815 USA

Phone: 800.325.3133, +1.570.389.5810

Outside the US: +1.570.389.5814

Fax: 800.452.0155, +1.570.387.7786

Email: info@sekisui-spi.com

Technical Service

Phone: 800.682.8758

Fax: +1.570.387.8722

Outside the US: +1.570.387.6997

techservice@sekisui-spi.com

sekisui-spi.com

Because we cannot anticipate or control the many different conditions under which this information and our products may be used, we do not guarantee the applicability of the accuracy of this information or the suitability of our products in any given situation. Users should conduct their own tests to determine the suitability of each product for their particular purposes. Data in the physical property table represents typical values and are to serve only as a guide for engineering design. Results are obtained from specimens under ideal laboratory conditions. Right to change physical properties as a result of technical progress is reserved. THE PRODUCTS DISCUSSED ARE SOLD WITHOUT WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, EITHER EXPRESSED OR IMPLIED, EXCEPT AS PROVIDED IN OUR STANDARD TERMS AND CONDITIONS OF SALE. Buyer assumes all responsibility for loss or damage arising from the handling and use of our products, whether done in accordance with directions or not. In no event shall the supplier or the manufacturer be liable for incidental or consequential damages. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Consult local code and regulatory agencies for specific requirements regarding code compliance, transporting, processing, recycling and disposal of our product. Product not intended for use as a heat resistant surface. Texture, product grade and other conditions may cause variations in appearance.

This information supersedes all previously published data.